

STUCCO

MARBLE FINISH

DECORATIVE PAINTS & COATINGS



COLORTEK®

Description

Colortek stucco is a decorative coating made from natural mineral materials that are trowel applied in a series of fine layers to create the polished, two-tone appearance of marble surfaces

Recommended For

To create a highly polished decorative surface on interior plaster, taped and jointed plasterboard, freshly plastered walls that are fully dry.

Key Features

- Environmentally friendly
- High gloss smooth finish
- Washable
- Hard durable polished surface
- Non-flammable
- No dirt pick-up
- Natural mineral material
- Good water vapor permeability

Physical Properties

Solvent Type	Water Based	
Finish Type	High gloss	based on ASTM D523
Spreading Rate	Approx. 0.4kg – 0.6kg/m	
Average Dry Time	Touch-dry in 1 hour	based on ASTM D 1640
Flash Point	Non-combustible	
Dry Film Thickness	100 – 150 microns	
Thinner	No thinning is required	
Adhesion	1.8 N/mm ²	based on ASTM D4541
Density	1.5 g/cm ³ (1.5 Kg/L)	
Solids	66%	
Viscosity	250,000 – 290,000 cP (Spindle 96/Speed 10)	
VOC	0.22 mg/m ³	
Bases	Can be tinted any color	
Pot Life	Unlimited	
Pencil Hardness	4H	
Shore D Hardness	70	
Scrub Resistance	> 10000 cycles	based on ASTM D2486
Impact Resistance	10 cm/Kg	based on ASTM D 279

THIS PRODUCT IS GREENGUARD GOLD CERTIFIED

The above-mentioned certification determines our products compliance with the following building codes and programs amongst others:

- CHPS 2.2.2: Paints & Coatings
- LEED 2008, LEED 2009 and LEED V4

This product is compliant with the following standards

- GS 11

COLORTEK®
Wall and Floor Fashion
info@colortek.eu
www.colortek.eu



STUCCO

MARBLE FINISH

DECORATIVE PAINTS & COATINGS



COLORTEK®

Surface Preparation

Never attempt to apply over wallpaper or lining paper. Great care should be taken on surfaces that are already decorated. A flat or true substrate is vital to achieve high quality results as any bumps or imperfections may show up in the finished surface. Great care should be taken when using Stucco on a substrate that it will tend to crack along any joints or that may also swell and warp such as MDF.

All surfaces must be cured, clean, dry, and free from dirt, dust, rust, stains, grease, oil, mildew, wax, efflorescence, bond-breakers and other contaminants. Remove all loose, peeling, or chalky paint by sanding, scraping, or any other appropriate methods. Repair all cracks, holes, and other surface imperfections with a suitable patching material. Repaired surfaces should then be sanded smooth, dusted clean and primed with a suitable Colortek primer.

New plaster or masonry surfaces must be allowed to cure (28 days) before applying base coat. Cured plaster should be hard, have a slight sheen and maximum pH of 10; soft, porous or powdery plaster indicates improper cure. Knife off any protrusions and prime the plaster before and after applying patching compound. Poured or pre-cast concrete with a very smooth surface should be etched or abraded to promote adhesion, after removing all form release agents and curing compounds. Remove any powder or loose particles.

CAUTION: Scraping or sanding surfaces of older buildings may release dust containing lead or asbestos. **EXPOSURE TO LEAD OR ASBESTOS CAN BE VERY HAZARDOUS TO YOUR HEALTH.** Always wear appropriate personal protective equipment during surface preparation and finish clean up of any residues by water-washing all surfaces.

Primer Systems

SURFACE TYPE	RECOMMENDED COLORTEK PRIMER
Drywall	Colortek Primer
Porous masonry	Colortek Sealer, Colortek Primer
Non-porous masonry	Colortek Primer or Colortek Undercoat
Wood	Colortek Undercoat or Wood Primer
Metal	Colortek Adhero, Adhero quick dry, SX47 StopRust, Aquazinc

Application Conditions

Do not apply at temperatures below 5 °C or when rain is expected.

Application Method

Apply using a Inox trowel, cover with successive coats of STUCCO until the desired finish is achieved. After 20 minutes of final coat, rub down with 2000 grade sand paper or press down with the trowel to get the final shiny effect.

Protect the decorative finish by using one of the available protective coats: Cera Wax, Aqua Wax or Metallic Wax.

Pack Size

- 1 US Quart – 1 kg
- 1 US Gallon – 5 kg
- 1 US Drum – 25 kg

Shelf Life

24 months from the date of production.

Storage and Handling

Care should be taken to avoid spillage. Store in a dry area. Protect from freezing. Extreme temperatures may cause paint to become unusable. For example: freezing and thawing may cause paint to gel, and high heat may cause solid skin to form.

Safety

Use under well ventilated conditions. Do not breathe or inhale spray mist or sanding dust. Avoid skin contact; spillage on the skin should immediately be removed with suitable cleanser, soap and water. In case of eye contact, flush immediately with water for at least 15 minutes and seek medical attention immediately. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

STUCCO

MARBLE FINISH

DECORATIVE PAINTS & COATINGS



Cleaning

Remove as much leftover product as possible from the application equipment before cleaning. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Do not empty product into drains or watercourses.

Technical Assistance

Available through your local COLORTEK® Design Center or through your COLORTEK PAINTS® authorized distributor. For the location of the retailer nearest you, email us at info@colortek.eu or check our website www.colortek.eu.

Disclaimer

Product batches are subject to stringent quality control checks in conformity with ISO 9001:2008, Certificate CH12/1128.

The information submitted in this manual is correct to the best of our knowledge & experience. No liability whatsoever can be accepted on the basis of the information supplied herein.